

INSTRUCTIONS

1. Original and/
2. Description of corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner OF SECTIONS 10, 11, 14, AND 15 T. 5N R. 13W P.M.M. DEERLODGE County

1. 1906 HENRY B. DAVIS AND EDWIN R. McLAIN

SET A PORPHYRY STONE, 12X10X5 INS., 8 INS. IN THE GROUND, FOR CORNER OF SECTIONS 10, 11, 14, AND 15, MARKED WITH 4 NOTCHES ON SOUTH AND 2 NOTCHES ON EAST EDGE; FROM WHICH


- A PINE, 5 INS. DIAM., BEARS N48°E, 55 LKS. DIST., MARKED T5NR13WS11BT.
- A PINE, 5 INS. DIAM., BEARS S25°E, 97 LKS. DIST., MARKED T5NR13WS14BT.
- A PINE, 12 INS. DIAM., BEARS S53°30'W, 63 LKS. DIST., MARKED T5NR13WS15BT.
- A PINE, 5 INS. DIAM., BEARS N75°W, 110 LKS. DIST., MARKED T5NR13WS10BT.

1969 B.L.M. ROY LEEDY

THE CORNER OF SECTIONS 10, 11, 14, AND 15, MONUMENTED WITH A GRANITE STONE, 14X10X8 INS., FIRMLY SET, MARKED 2 NOTCHES ON THE EAST, AND 4 NOTCHES ON SOUTH EDGES, AND WITNESSED BY THE REMAINS OF THE ORIGINAL BEARING TREES:

- A PINE, 12 INS. DIAM., BEARS N52°E, 55 LKS. DIST., MARKED T5NR13WS11BT.(RECORD N48°E)
- A STUMP, BEARS S25°E, 97 LKS. DIST., MARKED T5NR13WS14BT.
- A PINE, 15 INS. DIAM., BEARS S53°30'W, 63 LKS. DIST., MARKED T5NR13WS15BT.
- A DEAD PINE, 9 INS. DIAM., BEARS N75°W, 107 LKS. DIST., MARKED T5NR13WS10BT.(RECORD 110 LKS. DIST.)

AT THE CORNER POINT SET AN IRON POST, 30 INS. LONG, 2 1/2 INS. DIAM., 24 INS. IN THE GROUND, WITH BRASS CAP MARKED.



FROM WHICH

- A PINE, 6 INS. DIAM., BEARS S53°30'E, 22 LKS. DIST., MARKED T5NR13WS14BT.
 - A PINE, 8 INS. DIAM., BEARS N75°30'W, 18 LKS. DIST., MARKED T5NR13WS10BT.
- BURY THE ORIGINAL STONE ALONGSIDE THE IRON POST.

2. 1997 MIKE D. WELDON


FOUND A B.L.M. BRASS CAP ON 2 1/2 IN. DIAM. IRON POST, CAP MARKED AS SHOWN.

- A PINE, 12 INS. DIAM., BEARS N50°E, 36.5 FT. DIST., MARKED T5NR13W----
- A PINE, 10 INS. DIAM., BEARS S55°E, 14.7 FT. DIST., MARKED T5NR13WS14BT.
- A PINE, 22 INS. DIAM., BEARS S53°W, 41.7 FT. DIST., MARKED T5NR13WS15BT.
- A (NEAR DEAD) PINE, 10 INS. DIAM., BEARS N75°W, 71.2 FT. DIST., MARKED T5NR13WS10BT.
- A PINE, 10 INS. DIAM., BEARS N75°W, 12.0 FT. DIST., MARKED T5NR13WS10BT.

3. 1997 MIKE D. WELDON

BEARING TREE SIGNS WERE AFFIXED TO THE FRONT AND LAND SURVEY MONUMENT SIGNS TO THE BACK OF THE BEARING TREES. REGISTERED LAND SURVEYOR, "RLS 7692-S" WASHERS WERE AFFIXED TO THE SIDE CENTER OF THE BEARING TREES AT THE BASE.

ANGLE IRON POST WITH PROPERTY BOUNDARY AND LAND SURVEY MONUMENT DECALS SET 0.5 FT. NORTHWEST.



SKETCH OF CORNER

CERTIFICATION

I, JOHN K. BUNCE II
 certify the information shown herein is true and correct
[Signature]
 Signature Ground Party Chief

I, MIKE D. WELDON
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-72-101, et seq., M.C.A.)
[Signature]
 Signature of Surveyor & Seal

Date: 4-98 Reg. No. 7692-S
 Employer: U.S. FOREST SERVICE

Office of Clerk and Recorder, County of DEERLODGE. This "corner record" was filed for record on May 14, 1998 was noted on the cross-index plat and is assigned page No. 503 book No. 2
[Signature]
 County Official

