

CLASSIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Original record: July. 1873, Set a sandstone 12x10x7 ins., 7 ins. in the ground marked 1/4 on the north side.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work:.....Jan....,1991.....

Set a 3 in. aluminum cap on a no. 5 rebar marked as shown

Corner is under an East-West fence on the south side of the County Road.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Corner was set at record distance from Flint Creek; 2.94 chains or 194 ft. West of Flint Creek

DIAGRAM OF CORNER:

Surveyor's Seal

I, William D. Bayer.....
certify that the information shown herein is true and correct.

William D. Bayer
Signature of Ground Party Chief

N. T.6 N.R.14
S. 15 1/4
S. 22



I, William D. Bayer.....
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

William D. Bayer
Signature of Surveyor

+ = Corner recorded on the sheet

3321 S
Registration Number

Office of Clerk and Recorder, County of Grant

This "corner record" was filed for record on the 31st day of Jan, 1991, was noted on the cross-index plat and is assigned page No....., in book No.....

Jo Bayer
County Official

Cross Index No. N-15 T. 6 N R. 14 W Mer.

20440