

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner SOUTHEAST CORNER SEC 29 T. 6 N R. 25 E P.M.M. MUSSELSHELL County

RECORD: 1904 GLO SURVEY - "set a sandstone 18x12x5 ins 12 ins in the ground for the cor to Secs 28,29 32 and 33 marked with 1 notch on the S and 4 notches on the E edges....."

FOUND: A stone as described above firmly set in place 1 foot north of a barbed wire fence.

SET: A 5/8" X 24" rebar with a 1-1/2" aluminum cap was set at the north edge of the found original stone monument as a witness. Bearing trees were established in each section as shown in sketch below.

SEE ALSO CERTIFICATE OF SURVEY No. 1993-3

SKETCH OF CORNER

CERTIFICATION

I, Larry Resch
certify the information shown herein is true and correct.
Larry Resch
Signature Ground Party Chief

I, Peter B. Knapp
certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)
Peter B. Knapp
Signature of Surveyor & Seal

Date: 5/93 Reg. No. 8377-S
Employer: ENGINEERING, INC.

Office of Clerk and Recorder, County of Musselshell. This "corner record" was filed for record on the May 20 8:50 AM day of 1993 was noted on the cross-index plat and is assigned page No. _____, in book No. _____, in Jane E Mang Dyhema M Weigmann County Official

