

INSTRUCTIONS

1. Original and or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.


CERTIFIED CORNER RECORDATION

Corner S.E. Section Corner S 31 T. 18 N R. 27 W P.M.M. Mineral County

Record of previously filed corner recordation form: (Found)
 A Stone 8x8x11 ins. with 5 notches on E and 1 notch on W
 Left corner stone in place and placed a mound of additional
 stone around it. Marked new R.M. trees as follows. 6 ins Tam.
 Bears N 38° W 26.2' dist. which I mark R.M. 6 ins Tam. Bears
 S 70° E 10.6' dist which I mark R.M.

Found: Corner stone as described lying loose among scattered
 stones. Both R.M.s are alive and have healed blazes. Also found
 location tags lying on the ground beneath both R.M.s showing
 bearing and distance to corner. Distance on location tag for
 North R.M. is 26.9'. This distance matches the center of an
 8" Diam. hole believed to be formerly occupied by the corner
 stone and was used to reestablish its position.

To perpetuate this corner, a 2" Brass Cap on a 1"x24" pipe
 is set 10.6' from the South R.M. and 26.9' from the North R.M.
 The corner stone is laid alongside and a concentric mound of
 stone is formed around the corner.



SKETCH OF CORNER

CERTIFICATION

Morgan Smith

certify the information shown herein is true and correct.

Morgan Smith
 Signature of Ground Party Chief

H. James Smith

certify that this Corner Record correctly represents work performed
 by me or under my direction in compliance with the Corner
 Recordation Act, 170-22-101, et seq., M.C.A.

H. James Smith
 Signature of Surveyor & Seal

Date 6/2/83 Reg. No. 2740 S

Employer _____

Office of Clerk and Recorder, County of _____ This "corner
 record" was filed for record on the 27th June day of 1983
 at 2:30 pm.
 was noted on the cross index plat and is assigned page No. _____, in
 book No. _____
Donna Davis
 County Official

Sec.	
31	

61315

Cross Index No. Z-5 T 18N R 27W P.M.M.

• - corner this sheet