

CERTIFIED LAND CORNER RECORDATION

ORIGINAL GLO RECORD OF CORNER

Set a post 3 ft. long, 3 ins. square, 24 ins. in the ground for 1/4 sec. cor., marked 1/4 on S. and N. face, from which:
A pine, 12 ins. diam., bears N.55°E. 32 lks. dist., marked 1/4 S. B.T.
A balsam, 8 ins. diam., bears S.15°E. 6 lks. dist., marked 1/4 S. B.T.

EVIDENCE FOUND OF ORIGINAL CORNER

No evidence found. Corner was set from Washington Water Power Survey notes.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE LOCATION OF THIS CORNER

AT THE CORNER POINT:

Set 1/2 in. capped rebar (L.S. 4659 S) in concrete, from which:
A tamarack, 5 ins. diam., bears South 10.9 ft.
A tamarack, 10 ins. diam., bears S.60°W. 15.0 ft.



1/4 Cor., Secs. 5/8, T.23N., R.30W.


Surveyor's Seal



I, Kent E. Bauer
certify that the information shown herein is true and correct.

Kent E. Bauer
Signature of Ground Party Chief

DIAGRAM OF CORNER:
See reverse.



I, Carl R. McMillen
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Carl R. McMillen
Signature of Surveyor

T. 23 N., R. 30 W.

= Corner recorded on the sheet

DATE: October 25, 1978

L.S. 4659 S
Registration Number

VOL 1 PAGE 774

Office of Clerk and Recorder, County of Sanders

This "corner record" was filed for record on the 9th day of March, 1979, was noted on the cross-index plat and is assigned page No. 774, in book No. 1

see 50K

Deputy County Clerk Rose Byrd
County Official

Cross Index No. E-7 T. 23 R. 30 Mer.