## CERTIFIED CORNER RECORDATION

T. 33N R. 5W P.M.M. Glacie ... County

Record: Set a granite stone, 14x12x7 ins., 9 ins. in the ground, marked wy 4 notches on south, and 3 notches east. Raise a mound of stone, 2 foot base, 1/2 foot high west of corner (GLO, 1901)

Subsequent: Certificate of Survey #7B, indicates a found corner. No description of this "found" corner is given, nor is any corner record filed.

Found: At record position, no monument is found. Area is occupied by Meadowbrook Road & Field roads.

Set: Based upon measurements to adjacent corners, accept the centerline intersection of roads north-south-east-west.

Set a 5/8" rebor with Z" aluminum cap, flush to the

road surface. Cap marked:

133N R5W 59 510 10155LS

From which; Gus stand # 574 boars N71 E, 49.3 feet. Apower pole bears S45°E, 57.7 feet



<b>.</b>		
N Field road No Scale	5.9 5.10 Field road 5.16 xxxq road	CERTIFICATION  I. CAULA DOOLS  certify the information shown herein is true and correct.  Signature Ground Party Chief  I. Caula DOOLS  certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)  Signature of Surveyor & Seal  'Date: 1/2000 Reg. No. 1015545
Office of Clerk and B	SKETCH OF CORNER Pawer Pole	Sec. 9

SKETCH OF CORN	ER Power Pole	Employer:	
	: 122 A 12 A	This ''corner	Sec. 9
Office of Clerk and Recorder, County of	The American State of the Control of		
record" was filed for record on	in the same of the		
WAS noted on the cross-index plet and is STATE OF MONTANA GLACIER COUNTY RECORDED: 05/12/2004 12:13 MISC F SYLVIA BERKRAM CLERK AND RECORDE	ILED	DOC #:	254657 T
	Cross Index No.	T. 33N R. SW PMM	• - corner this shee