INSTRUCTIONS 1. Original and/or subsequent record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

Bescription of monument and accessories set to perpetuate the corner position

Sector of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

_____T.<u>4S____R._8E___P.M.M._Park</u> Corner 13, 14, 23, 24 ____County

1) Original GLO survey of 1874 by T. Benton Post: Set a basalt stone 17x6x5", 12" in the ground for cor. to sec.13,14,23,24, marked with 3 notches on the S. and 1 on the E. edges.

Found no evidence of the original corner monument. I did find an 2) aluminum cap in a mound of stones as described and set according to the recordation filed by Dennis Foreman in 1993. After finding the original bearing tree for the section corner 1 mile to the west; and finding the original stone 1 mile to the north, I do not accept the corner position indicated by Foreman's cap. I instead use a four way proportion using the 2 above mentioned corners, and the section corners used by Foreman to the east and south.

3) I did not monument this corner. The aluminum cap set by Foreman serves as a reference monument. It bears S 63° 33' 44" E, 46.33 ft.

(See reverse side for corner ties)

SEC.14	5EC.13	CERTIFICATION I. JCe E. Ellef Scur certify the information shows herein is true and correct.
		Signature Ground Party Chief 1. DONATHON D. PALIMIE (R certify that this Corner Record correctly represents work performed
NO SCALE SEC. 23	ALUMINUM CAP SET FOR SECTIO CORNER BY FORE USED A	by me or under my direction in compliance with the "Corner Recordation Act, v(0.22-101, et eeg., M.C.A) MAN
	SKETCH OF CORNER	Employer:
Office of Clerk and Recorder, County of <u>Park</u> . This "corner record" was filed for record on <u>Cucquest 1, 1995</u> 3:45 pm		
was noted on the cross-index plat and is assigned page No. 326 , in $-+-+-+-$		
book No. <u>One</u> No fee	247592 Denise Nol County Off	ficial -T. <u>HS_R_8E_PMM</u> • - corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

