CERTIFIED CORNER RECORDATION Corner_W 1/4 SECTION 17 T. 32N R. 23E P.M.M. BLAINE County

ORIGINAL RECORD: (GLO - 1890, Page) Set a limestone 14 x 8 x 6 ins. 10 ins. in the ground for 1/4 sec. cor., marked 1/4 W. face; dug pits 18 x 18 x 12 ins. N. and S. of stone, 5 1/2 dist. and raised a mound of earth 1 1/2 ft. high, 3 1/2 ft. base alongside.

SUBSEQUENT RECORD: (Sands Addition-1899, Barton Addition-1904, Plat of Blocks 1 & 2 Sands Addition-1956 and RR maps) Numerous Addition maps and RR maps show ties to this corner although it is unclear what it is.

EVIDENCE FOUND: (August, 2007) No original evidence was found or other monuments per the subsequent records.

PERPETUATION: (August, 2007) Held a computed position per intersection monuments found at Central and South Avenue with Mitchell Street and Sands Street. This position also fits very well with a tie to the centerline of the railroad. At this position, set a 5/8" rebar and 2" aluminum cap, marked as shown, flush with the pavement. Set references as shown below.

SEE ASSOCIATED CERTIFICATE OF SURVEY - SEC. 8, T.32N. R.23E.



P+#310 (309 '320 ROP MONS