## INSTRUCTIONS

d/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterates.

corners.

3. Description of monument and accessories set to perpetuate the corner position.

4. Sketch of corner, show all perlinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

5. Certification must be signed and scaled by Land Surveyor registered in the State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner Northwest Cor Sec 5 T. 1 N., R. 58 E. P.M.M. Carter County

ORIGINAL RECORD: Surveyed by George Scheetz in 1889.

Set a sandstone 20x16x5 ins. 15 ins in the ground for sec cors. 5, 6, 31, and 32, marked with 1 notch of W. and 5 notches on E. edge; and raised mound of stone along side.

162713

SUBSEQUENT RECORD: Dependently resurveyed by W.R. Bandy & Earnest Parker in 1933.

> the cor. for secs. 5, 6, 31 & 32, which is a sandstone 14x9x2 ins. lying on the ground just N. of corner post of fence, marked and witnessed as described in the offical record. With old corner stone alongside and just N. of fence corner,

Set an iron post, 3 ft long, 3 ins. diam., 28 ins. in the ground, with brass cap marked:

> **T2N R58E** S31:S32 ---!---S6 | S5 T<sub>1</sub>N 1933

FOUND : Brass cap marked as per subsequent record.

SET : Monument in good repair nothing new set.

BC 10' ABOUE GROUND		I Quinn Wright certify the information shown Signature Control of the Record by me or under my directif Record that this Confer Record to Act of the Record	round Party Chief
SKETCH OF CORNER		Employer: Prairi	e States/HKM
Office of Clerk and Recorder, Count record' was filed for record on		This "corner	Sec. 5
was noted on the cross-index plat ar	ond is assigned page No.  Samufa County Of	aslleberry ficial	
	Cross Index No. A - 5	T. IN R. 58E PMM	• - corner this sheet