INSTRUCTIONS

1. Gri .id/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

Corners.
Description of monument and accessories set to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner East Quarter Cor. Sec 4 T. 1 N., R. 58 E. P.M.M. Carter County

ORIGINAL RECORD: Surveyed by George Scheets in 1889.

Set a sandstone 17 x 12 x 10 ins. 11 ins in the ground for 1/4 Sec. Cor. marked 1/4 on the west face, dug pits 18 x 18 x 12 ins N & S of stone 5 1/2 ft. dist. and raised a mound of earth 1 1/2 ft high, 3 1/2 ft base alongside.

162708

SUBSEQUENT RECORD: Dependently resurveyed by W.R. Bandy and Ernest Parker in 1933.

> at the proportionate point for the 1/4 cor. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap marked:

1/4 1 \$4153 . 1933 Dig pits 18x18x12 ins N. & S. of cor.

FOUND : Brass cap marked as per subsequent record. with fiberglass post as a witness post 1.5 ft south of cor.

Monument in good repair. nothing new set. SET :

· ``			
Fiberglass WP SKETCH OF CO	DRNER	I, Quinn Wright certify the information shown h 2	Sund Paris and
Office of Clerk and Recorder, County	of Carter	This ''corner	Sec. 4
record" was filed for record on October 9, 1990			
was noted on the cross-index plat and is assigned page No, in			
book No	(Samila) Castle County Offic	cheny	
162718		<u>г. IN R. 58Е рмм</u>	- corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors