172271

Carter

CR FILE

INSTRUCTIONS 1. Original and/or subsequent record used to evaluate the corner position.

- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- Bescription of monument and accessories set to perpetuate the corner position.
 Sketch of corner, show all pertinent data which can best be shown in sketch example, corner marking, topography ties, position of accessories, etc.
- Certificaton must be signed an sealed by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: NW Corner Section 19

____ T. ___1 N. ___ R. ___59 E. ___ P.M.M. ___

County

RECORD:

1933 - Resurvey by William R. Bandy and Ernest Parker: "Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, with brass cap marked,



dug pits, 18x18x12 ins. in each sec., 3 ft. dist."

FOUND:

April, 2005 - GLO brass cap monument firmly set 8 inches above ground, marked as shown above.

Location poster on 8 in. corner fence post bears N. 86° E., 31.7 ft.

Loacation poster on 4 in. fence post bears N. 24° E., 87.0 ft.

PERPETUATION:

Set a 5-foot red angle iron post with 54-2 and 54-9 decals alongside corner.

Corner falls in open field west of fence intersection.

See Certificate of Survey No. _____ for adjacent corner ties.



172271