CERTIFIED CORNER RECORDATION Corner <u>1/4 24</u> T. <u>4 S.</u> R. <u>50 E.</u> P.M.M. <u>Powder River</u> County

<u>1908 Original GLO record by George L. Elmer and Theodoor O. Johnston, Book 5662 Page 13</u> "Set a sandstone, 12 x 10 x 5 ins., 8 ins. in the ground, for 1/4 sec. cor., marked 1/4 on W. face; and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor."

1992 Remonumentation by S. R. Smith

Found stone, 13 x 13 x 6 ins., 8 ins. in the ground, "1/4" fainly visible on Northeast face. At the position marked by the stone, set an aluminum pipe, 2 1/2 ins. diam., 30 ins. long, with 3 1/4 ins. diam. M.D.T. aluminum cap, marked as shown below. Buried the stone alongside monument and raise a collar of stone around monument.

Established two references:

An aluminum nail in brace post, north side, 2 ft. above ground, bears S.83°E., 8.47 ft. dist. An aluminum nail in brace post, west side, 2 ft. above ground, bears S.3°W., 8.52 ft. dist.

Set a galvanized steel witness post, 6 ft. long, with M.D.T. sticker attached, bears South, 1.0 ft. dist.

Measurements were made with a Silva hand compass (declination 13°E.) and a steel tape.

Refer to Certificate of Survey filed in conjunction with this corner recordation for ties to other section controlling corners in this area.



0C302