CERTIFIED CORNER RECORDATION 1/4 T. 4 S. R. 51 E. P.M.M. Powder River County 19 20 Corner

i j programa services

<u>1908 Original GLO Record by George L. Elmer and Theodoor O. Johnston, Book 5664 Page 34</u> "Set a sand stone, 20x12x10 ins., 15 ins in the ground, for 1/4 sec. cor., marked 1/4 on W. face; dig pits, 18x18x12 ins. on line N. and S. of cor. 3 ft. dist., and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.

1992 Remonumentation by S. R. Smith

No original evidence found. Proportional location falls 8 ft. south of an angle break in a North-South fenceline.

At the proportional location, set an aluminum pipe, 2 1/2 ins. diam., 30 ins. long, 25 ins. in the ground, with 3 1/4 ins. diam. M.D.T. aluminum cap, marked as shown below. Raised a collar of stone around cap.

Established two references:

An aluminum nail in fence post, north side, 2 ft. above ground, bears S.63'E., 32.56 ft. dist. An aluminum nail in fence post, west side, 2 ft. above ground, bears N.11'W., 9.45 ft. dist.

Set a galvanized steel witness post, 6 ft. long, with M.D.T. sticker attached, bears North, 1.5 ft. dist.

Measurements were made with a Silva hand compass (declination 13°E.) and a steel tape.

Refer to Certificate of Survey filed in conjunction with this corner recordation for ties to other section controlling corners in this area. S18 S17



OC202