- INSTRUCTIONS
- Original and/or subsequent record used to evaluate the corner position. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

Corner	‡ Cor. Sec. 29 & 28	RR.	Powder River P.M.M	County
	1998 Record		· · · · · · · · · · · · · · · · · · ·	
	We did not have a copy of t of T4S, R51E by Geo. L. Elm			
	1947 Record			

1947 G.L.O. resurvey & remonumentation of T4S, R51E by Ranney Y. Lyman.

The $\frac{1}{4}$ cor. of secs. 28 & 29, marked by a broken sandstone and distinct pits.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap marked and bury the old stone beside the iron post, and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of corner.

1992 Found

Found iron post with brass cap as described in the 1947 G.L.O. notes and marked as shown below. Found broken stone lying directly south of cap, no evidence of mound of stone.

<u>1992 Set</u>

Compared



т9

Cross Index No.

T. 45 R. 51E PMM

corner this sheet