CERTIFIED CORNER RECORDATION

Corner SEC 7,8,17,18 T. 5 N., R. 9 W., P.M.M. ANACONDA-DEER LODGE County

Original: GLO SURVEYORS, AUGUST 1868

SET A POST IN A MOUND OF EARTH, WITH PITS, CHARED STAKE AS PER INSTRUCTIONS

IN WILLOW THICKET

Subsequent: NONE

Evidence: NONE

Perpetuation: SET 5/8" x 24" REBAR WITH 2" ALUM. CAP, MKD. MILAM 9007

ESTABLSIHED CONER POSTION BY DOUBLE PROPORTION MEASUREMENT

SET 5' STEEL FENCE POST , CORNER POSTION FALLS 11.0 FEET IN

WARMSPRINGS CREEK FROM THE NORTH BANK, SET MONUMENT AT CREEK

BOTTOM ELEVATION, ROCK RINGED,

ESTABLSHED THE FOLLOWING REFERENCE MONUMENT; SET 5/8" REBAR WITH 2" ALUM CAP MKD MILAM, 9007

N 50°22′53"E, 34.42 FEET S 39°12′29"E, 65.57 FEET S 52°06′28"W, 51.07 FEET N 24°52′47"W, 31.32 FEET STAMPED "T5N, R9W, S 8 1994" STAMPED "T5N, R9W, S 17 1994" STAMPED "T5N, R9W, S 18 1994" STAMPED "T5N, R9W, S 7 1994"

See Certificate of Survey Number 206-A for further information





| CERTIFICATION | | | | |
|--|--|--|--|--|
| ,James Nelson | | | | |
| certify the information shown herein is true and correct | | | | |
| Camp Nelson | | | | |
| Signature of Ground Party Chief | | | | |
| I, Ronald D. Milam | | | | |
| certify that this Corner Record correctly represents work performed by | | | | |
| me or under my direction in compliance with the "Corner Recordation Ad | | | | |
| (70-22-101, et seq., M.C.A.) | | | | |
| Ronald D. Milam | | | | |
| Signature of Surveyor & Seal | | | | |
| Date: | | | | |
| Employer: D J & AMISSOULA , MONTANA | | | | |
| 0-4 10 | | | | |

Sketch of Corner

| Sketch of Come | | | | Section 18 |
|--|------------------|---------------|---------|---------------|
| Office of Clerk and Recorde This "corner record" was fil was noted on the cross-inde in book No. | ed for record on | | | |
| Conso Indox No | 1 - 5 | T. 5 N., R. 9 | W., PMM | • THIS CORNER |