INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

corners.

corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION 21 | 22 28 27 _ T. __<u>5N</u>___R. <u>_9W</u>____P.M.M. <u>DEER LODGE</u>____County Corner .

1869 - W. W. Johnson 1. a)

> Set Corner to Sections 21, 22, 27 and 28, a granite rock, 22 X 14 X 10 ins., with pits, marked stone as per instructions.

b) 1967 - S. J. Skousen

At the corner point for Sections 21, 22, 27 and 28 (T5N R9W, P.M.M.), I find a 4-way fence intersection (fences running cardinal directions) with the southern fence offset, as shown:



A well-set stone with three notches on the West and two notches on the North was found at the position indicated. This agreed with record.

At the corner point I set a 2 ins. X 3 ft. galvanized iron pipe, 18 ins. in the ground, bury original stone alongside, and stamp the brass cap as shown:



No new reference monuments are within limits.

Corner No. 1 of National Mineral Claim, MS 9549, bears S. 50° 45' E., 368.71 ft. This corner is an iron post with brass cap.

2. 1988 - Michael D. Weldon

I found S. J. Skousen brass cap as officially described.

	CERTIFICATION
ONT	I,
MICHAEL C WELDON 7992 S SURVENUM	Signature Ground Party Chief 1. Michael D. Weldon certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70,424101, et seq., M.C.A.) Michael D. Weldon Signature of Surveyor & Seal Date: 4/92 Reg. No.7692-S
SKETCH OF CORNER	Employer: USDA, Forest Service
Office of Clerk and Recorder, County of DEER_LODGE This "corner record" was filed for record on APR 14 1993 was noted on the cross-index plat and is assigned page No, in book No By Manan & Atribuk, Aprt, County Official	
Cross Index No. R-13 T. 5N R. 9W PMM • - corner this sheet	

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors