

INSTRUCTIONS

al and/or subsequent record used to evaluate the corner position. ription of evidence found, note discrepancies in the record, state method of establishing lost or obly

A stription of evidence sound, accessories set to perpetuate the corner position.
Description of monument and accessories set to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

٦ĺn

CERTIFIED CORNER RECORDATION

Corner \$ 30/29

_____ T. __5N_____ R. __<u>10W</u>_____ P.M.M. __Deer_Lodge__

County

Record 1868 - Set 1 sec. cor., a post in mound of earth with pits, charred stake and as per instructions.

Record 1959 - Montana Department Right-of-Way Plans for FAP S-304(2) indicates by symbol a found monument at the 1 Corner position 57.5' Rt. of centerline station 105+73.8.

Found 1987 - At the record station and distance right of centerline, found a 1" diameter iron pin bent over. The iron pin was firmly set and when straightened out was 6" above ground.

I accept the found Iron pin as evidence of $\frac{1}{2}$ located by persons unknown. At the corner position set a $3\frac{1}{4}$ " x 30" Alum. monument over the found iron pin, marked as per diagram below, 24" in the ground from which:

> A metal fence post witness bears NE,1' foot A fence post with MARLS Yellow Tag bears N 33°E, 2.6' feet A fence post with MARLS Yellow Tag bears S 5°E, 14.4' feet Corner is 1.5 feet west of east R/W Fence

See Corner 29, 30, 31 and 32 for Ties to other Corners.

