110845

## CERTIFIED LAND CORNER RECORDATION

| 1.       | DESCRIPTION 0<br>Corner to Sections                   | F CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)<br>5, 6, 7, 8, T.5N., R.1OW.         |
|----------|---|--|
|          |   | at fence corner used as section corner in survey filed<br>of Book 16 of Deeds. (fence N & W) |
| _        | Record: Post with p                                   | its and mounds.  |
| 2.       | 1/4 Corner between<br>Found: Shallow pit              | Section 6 & Section 5 T.5N., R.10W.<br>with low mound to North - remains of charcoal in edge |
|          | of mound. (   | fence N & S)   |
| з.       | Corner to Sections                                    | its and mound and charred stake.<br>5 & 6, T.5N., R.10W., & Sections 31 & 32 T.5N., R.10W.   |
|          | Found: Fence corne                                    | r fitting land calls to South but not to North (3 chains                                     |
|          | Record: Post with p                                   | its other corners on this township line. (fences N, S, $\&$ its and mounds.                  |
|          |   |  |
|          | DESC  | RIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  |
|          |   | ERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:  |
| 1.       | No further monument                                   | Date of work: Dec. 197   |
| ¥ •      |   | · · · · · ·  |
| 2.       | Set 5/8" x 24" reba<br>and raised mound of            | r with yellow plastic cap marked "ALPHA ENGRS 1888 ES" stone around the pin.                 |
| з.       | Set 5/8" x 24" reba                                   | or with yellow plastic cap marked "ALPHA ENGRS 1888 ES"                                      |
|          | and raised mound of                                   | stone around the pin.  |
|          |   |  |
|          |   |  |
|          | SKETCH, WITH COURS                                    | E AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.                             |
|          |   | Y SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)   |
|          | sis of Bearing is                                     | 2122 511 16  |
|          | e South Half of the<br>st side of Section             | 6 2637.31 60 S 00 <sup>6</sup> 34'25"W/<br>Z 2649.96'  |
|          | T.5N., R.10W.,<br>cord N 0-04 W                       | 1- 1/4   |
| Net      |   | center 14 589°19'59"E 685<br>2622.69'  |
|          | 1   | 2622.69' S 00° 30' 41 W  |
|          | Ν   | 5 00 38 41 W   |
|          | 1   |  |
|          |   | <u>CEE<sup>c</sup>39'10'E 65</u><br>7 2610.81' 78  |
| <u> </u> | <u> </u>  | DIAGRAM OF CORNER:   |
|          | Surveyor's Seal                                       | I, David M. Albert. T.S.N., R. IOW   |
|          | ANNE BRADD  | correct  |
|          | NTAA  | David M. albert  |
|          |   | Signature of Ground Party Chief  |
|          | CASHELL S   | I, John C. Cashell<br>certify that I have carefully performed or reviewed the                |
|          | 1888ES  | work done on the diagrammed corner as reported on this                                       |
|          | A GISTER SE   | recordation form and approve the same.   |
|          | JOHN C.<br>CASHELL'<br>1888ES<br>PEGISTERE<br>SALANIA | Signature of Surveyor  |
|          |   |  |
|          |   | 1888 ES<br>Registration Number   |
|          | -   | N $N$ ,  |
| 01       | ffice of Clerk and Recorder, Count                    | of Reer it rdge  |
| TI       | nis "corner record" was filed for a                   | ecord on the 3/24 day of farmany 19 8, was noted on the cross-index plat an                  |
|          | signed page No  |  |
| đ        | 3 Form 125-7887                                       | Cross Index No. A-5 C-5 T. 5/V R. 10 W   |