

INSTRUCTIONS

INSTRUCTIONS and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or ot

corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography tles, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet. corners.

CERTIFIED CORNER RECORDATION

County ___ T. <u>__5N ____</u> R. <u>__10 & 11</u> RM.M. <u>__Deer_Lodge ___</u> Corner 25 30 31 & 36

Record - 1868 - Set cor. to sec. 25, 36, 30, 31 a post in mound of earth with pits marked stone and as per instructions.

Record - 1899 - Set a quartzite stone, 18x12x6 ins., 12 ins. in the ground, for cor. of Secs. 25, 30, 31 and 36; marked with 1 notch on S. and 5 notches on N. edges and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Found 1987 - A quartzite stone 17" x 14" x 6", 6" above ground marked with one groove on south and 5 grooves on north with collar of stone.

At the position of the found corner movement, set a $3\frac{1}{4}$ " x 30" Alum. Monument, marked as per diagram below, 24" in the ground and bury original stone upside down along North side; raise a collar of stone painted yellow and set a metal fence post witness one foot South.

See Corner 29, 30, 31 & 32 T5N R10W for ties to other corners.

	CERTIFICATION
STATE OF MONTAN	I,
$ \begin{array}{c} $	Robert S. Custer million and the second party of the second party
MENT OF HIS	Date: 10/2/87 Reg. No. 33255 ACGISTERED ON IN
SKETCH OF CORNER	Employer: MDOH
Office of Clerk and Recorder, County of <u>Aur. Lodge</u> . This "corner Sec. 30	
record" was filed for record on <u>Novembur, 4, 1987</u>	
was noted on the cross-index plat and is assigned page No. 267 , in 56	
book No2 Linio Aarris Ileputy	
Cross Index No. V-1	T. <u>5N</u> R. <u>10W</u> PMM - corner this sheet

BC:vmd:52/c Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors