INSTRUCTIONS

r subsequent re-evidence found,

used to evaluate the corner position. discrepancies in the record, state method of establishing lost or obliterated

corners. 3. Description of monument and accessories set to perpetuale the corner position. 4. Sketch ef corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography lies, position of accessories, etc. 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana. 6. Fill in Cross index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION 1|6 12|7 Corner____SECTION CORNER T. 5 N. R. 10 & 11 W.P.M.M. ANACONDA-DEER LODGE County

RECORD;

GLO (1868) Set cor. to sec. 1, 12, 6, 7, a post in mound of earth with pits marked stone etc. as per instructions.

GLO (1899) Set a sandstone, 26x16x9 ins., 21 ins. in the ground for Cor. of Secs. 1, 6, 7, 12, marked with 5 notches on S. and 1 notch on N. edges, and raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor., Pits impracticable. CERTIFICATE OF SURVEY NO.S 110586, 41-B, 202-A, 203-C

Stone, found. FOUND:

Found sandstone, 5"x9" 7" above ground with 5 notches on S. & 1 notch on N. edges, in EAST-WEST fence line.

See Certificate Of Survey No. 214-D 215-C

	Signature of other in the second seco	NTAA BROON E RENSON Christianse word performed christianse with the Schwar MCA
SKETCH OF CORNER	Employer: GORDON SORENSC	IN ENGINEERING
Office of Clerk and Recorder, County of	This [®] corner day on 19 .	Sec. 12
was noted on the cross-index plat and is assigned page No.	<u>437</u> , in	
book No Darlana County Offi	aughn Depury	
Cross Index No. E-25	T. 5 N. R. 11 W? PMH	- corner this sheet