## **CERTIFIED LAND CORNER RECORDATION**

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)  $\frac{1/4 \text{ Corner between Sections 21 and 28, T.5N., R.12W., P.M.M.}{\text{Found: a 2<sup>1</sup>/<sub>2</sub>" pipe with a B.L.M. brass cap marked <math>\frac{21}{28}$  set in a mound of stone.

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

> > Date of work: Nov. 1977

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

DIAGRAM OF CORNER: Surveyor's Seal I, <u>George W. Baxter</u> certify that the information shown herein is true and N. correct. George Lu Bayter 28 Signature of Ground Party Chief JOHN C. John C. Cashell I, .. certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this CASHELL 1888ES Pmm 5.N RIZW, HIMMAN CHEER & recordation form and approve the same Corner-recorded on the sheet X U Signature of Surveyor 1888 ES Registration Number ET. Office of Clerk and Recorder, County of Piler Ar 65 This "corner record" was filed for record on the 25.... day of ... Janu . 19/.4 was noted on the cross-index plat and is 89....., in book No...... assigned page No ..... 12 County Official f Gene 3 Form 125-7887 Cross Index No. K-11 T. 5N R 12 Mer.