## INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
   Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
   Description of monument and accessories set to perpetuate the corner position.
   Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
   Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
   Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED	CORNE	ER REC	ORDATION
-----------	-------	--------	----------

CORNER	EAST 1/4 SECTION 17 T 5 N R	13 W	_ PMM	ANACONDA- DEER LODGE	COUNTY
RECORD:	BLM DEPENDENT RESURVEY, JULY 11 TO SEPT 25, 196	57			
	T5N  1/4 S17  R13W  FROM WHICH: A PINE 10 INS DIAM., BEARS S 41 ½ °W, 43 LKS A PINE 6 INS DIAM., BEARS N 12 ½ °W, 54 LKS	IE GROUND	, WITH BI	RASS CAP MKD.	
FOUND:	3 1/4 IN BRASSCAP, 5 IN ABOVE GRND MARKED AS SHO	OWN			
	10" PINE BT BEARS S 41° W, 43 LKS (28.4 FT) 6" PINE BT BEARS N 12° W, 54 LKS (35.6 FT)				
SET:	NOTHING				
NOTE:	ALL DISTANCES NOTED FOR BEARING TREES ARE HOTHE TREE TO THE MONUMENT  SKETCH OF CORNER	ORIZONTAL	, DISTAN(	CES FROM THE C	GREG A
	6" PINE  35.6 (54 LXS)  3 1/4 IN BRASSCAP STAMPED AS SHOWN  10" PINE	I, certify perform the "Co	Sign that this Corner by me or other Record Sign 10/17/200	Greg LaZerte, Lazerte, Laner Record correctly runder my direction is ation of Surveyor & Sature of Surveyor & Satu	Seal  14725LS
Office of Clerk and Recorder, County of DEER LODGE . This "corner				comer	.17
was noted on the cross-index plat and its assigned Page No. 557 in  Book No. 2 Deputy  Country Official					
	Cross Index No. L-9 T 5N	R /	3N PM	м • - C	omer this sheet