CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND AND ORIGINAL RECORD, IF KNOWN: Q.L.O. SURVEY COMMENCED 6-26-1903 RECORD: A POST 4"SQ. SETTING IFT ABOVE GROUND MARKED AND WITNESSED AS DESCRIBED BY THE SURVEYOR GENERAL

FOUND: NO EUIDENCE AT OCCUPATION

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE COBNER:

DATE OF WORK 10-92 SET: A 2" GALVANIZED CAP ON 1/2 X 24" FRON PIPE

SKETCH WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY: (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE)



I, Gordon E. Sorenson certify that the **DIAGRAM OF CORNER** Surveyor's Seal information shown herein is true and correct, and further certify that I NTAA have carefully performed or reviewed the work done on the diagrammed GORDON E. corner as reported on this recordation SORENSON form and approve the same. 2345 ES dated: ^c Gordon E. Sorenson, PE/RLS Montana Reg. No. 2345ES GR. & LANG _dated: Field Party Chief Office of the Clerk and Recorder, GRANITE County, State of Montana: This "corner record' was filed for record on the ______ day of ______ was noted on the cross index plat and is assigned page No. ______ in book No. _______ _, 199<u>'7</u>, Hanche Rederson Time: М. COUNTY OFFICIAL CROSS INDEX NO. X-/ , T. 5N, R. 14W, PMM 34788