INSTRUCTIONS

1. Original and/o. subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

3. Description of monument and accessories set to perpetuate the corner position

Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

6 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner W.C. 1 Cor. Secs. 2 & 3 _ T. _ 55 R. 51E P.M.M. Powder River County

1885 Record

We did not have a copy of the original 1885 G.L.O. survey notes of the subdivisions of T5S, R51E by George Scheetz.

1939 Record

1939 G.L.O. resurvey & remonumentation of T5S, R51E by Ranney Y. Lyman.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to the $\frac{1}{4}$ sec. cor., with brass cap 42.56 marked....

....and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

1992 Found

Found iron post with brass cap as described in 1939 G.L.O. notes and marked as shown below. Post is now 33 ins. in the ground, and no evidence of a mound of stone. 1939 notes show unsafe to set actual $\frac{1}{4}$ cor., as it would be along bank of the Powder River. Found steel fence post, 1.0 ft. N.W. of post, 3.0 ft., out of the ground, and put decal on it.

OWDER RIVE A60 1940) in shirohi uq Geng inda .11.1 man man " LUS KIMES The Crops Index 10.61 (1.1.194) 26 TO FENCE ħ£. PAP GRAVEL WITNESS woodt h ENCE -\$100 AL 16 Contraction of N MUS ATTOMU The ways such a fourth to the horizontal to the to で発展にもれたりにという الالبطوي المناقحين ومهيكا الطهين 8. 139. - 9.184 CERTIFICATION Douglas J. Martin 1.444 and correct. certify-the information show n certify th erformed by me o difection íth 🖞 'Corner Q~ 0.60% 81 G. A 1961 - 18 92 Reg. No. Date: 939 o 14 MDT 1-36 633 Employer: SKETCH OF CORNER Sec. B 182. 1. 1. 18 18 Office of Clerk and Recorder, County of Powder Prive . This "corner record" was filed for record on November 2, 1992 @ 10:22 AM was noted on the cross-index plat and is assigned page No. 118581 _, in 14400 (金田市)44-5 - 1-1-44-5 - 1-5-4-5 (onsidine), Deputy anole book No. -0340 County Official Indexed Cross Index No. W.C. - C17 T. 55 R. 51E PMM corner this sheet Compared N

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors 108