INSTRUCTIONS

Original and/or subseque _______.ecord used to evaluate the corner position.
Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

Description of monument and accessories set to perpetuate the corner position.
Description of monument and accessories set to be protected to be accessible and accessories and accessories are to be protected to be accessed and accessories are to be accessed and accessed and

Description of monument and accessories set to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

CORNER North East SEC. 14, T. 5 S., R. 51 E., P.M.M, Powder River COUNTY

ORIGINAL RECORD: Surveyed by George Scheetz in 1885.

SUBSEQUENT RECORD: Dependent Resurvey by Ranney Y. Lyman in Oct-Nov, 1939.

Proportional point for the cor. of secs. 11,12,13 & 14. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11,12,13 & 14, with brass cap marKed

T5S	ļ	R51E
S11	1	S12
	- : -	
S14	1	S13
19	23	9

and raise a mound of stone, 2 ft. base, 1% ft. high, W. of corner.

FOUND:

Brass cap and iron post lying on top of ground. No sign of mound of stone. Re-established corner by double proportionate measurement, using the found 1/4 corners to the north, south, east and west.

SET:

Set a standard MDT 34" alum. cap on a 24' x 30" alum. pipe, 24" in the ground. Placed a mound of stone around cap. Placed a 5%′ galv. steel witness post 3° SW of monument. Buried found brass cap upside down along the west side of new monument. New cap stamped as shown



X X WEST SS.S' A80 NP OLD BC WP	CERTIFICATION I, Ouinn Wrightunner certify the information shown hereinite true and correct. Signature Ground Party Cide I, Jimmie Je, BREAMOR certify that this Corner BREAMOR to runder my direction in compliance with The "Corner Recordation Act" (70.22-10), et seq. M.C.A.) Signature of Surveyor & Sequ Signature of Surveyor & Sequ Signature of Surveyor & Sequ Date: 12/17/92 Reg. No. 44555			
SKETCH OF CORNER	Employer: HKM ASSOCIATES			
Office of Clerk and Recorder, County of Powder River record" was filed for record on March 17, 1993 @ 10	:08 Am			
was noted on the cross-index plat and is assigned page No. <u>118811</u> , in				
book No (arcle R (onsidine) Deputy Indexed				

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors