CERTIFIED LAND CORNER RECORDATION

 DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)
 Corner to Section 28, 29, 32, 33 T6N, R13W Record: Quartsite stone 20x14x6 ins., 15 ins. in the ground marked 1 notch South and 4 notches East. BTs - N12E 2 1ks., S59E 33 1ks., S13¹/₂^OW 38 1ks., N57^OW 44 1ks.
 Found: Stone 10"x7"x10" above ground marked 1 notch South and 4 notches East & 4 BT (3 original and 1 extra from some unrecorded survey)
 A Corner between Sections 32 & 29 T6N R13W Record: Pine post - pits and mound - 1 chain west of creek Found: No evidence

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1979

We set 30"x2" galvanized pipes with brass caps marked with corner information date, and 1888ES. Also set a red fiberglass post with attention sign along-side each monument.

- 1. BTs 13" pine N19^OE 13.4 ft. (found but not original); 15" pine S62^OE
 20.8 ft.; 15" pine N55^OW 29 ft.; 9" pine (dead) S11^OW 24.5 ft.
- No trees near enough for BTs This corner was set by single proportionate measure.

