CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

ORIGINAL RECORD:

Set a sandstone 22x12x6 ins., 16 ins. in the ground for corner to sections 15, 16, 21 and 22. Marked with 3 notches S. and 3 notches E. Pits being impracticable, raised a mound of stone north.

FOUND:

No evidence remains of original monument. Accept a N-S-E-W fence intersection as the best remaining evidence of the corner position,

DESCRIPTION OF MONUMENT AND ACCESSORIES DEFAULTION	41~1A-55
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNERS	

At this point;

Set an iron post 21 ins. diam., 30 ins. long, 24 ins. in the ground, 1.5 feet north of the fence intersection, with brass cap marked:

CSSS

Set a 2x3x24 ins. wooden post on south side of corner.

гбн	R20E	٧ì
16	15	2
21	22	Ž,
19	77	Ď

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

3	10	S01 ⁰ 36145''E	15 22
4	9	10,574.41	16 21

Bearing Base: North Line, NEX, Sec. 2, T.6N., R21E. (N83°37'W)

Surveyor's Seal

ssigned page No.

orm 125 - 45227

T. Jorgen Embreus I, .. certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, Gerald P. Russell certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same,

Kusser

Signature of Surveyor (hristian, Spring, Sielbach & Assoc. Billings, Montana 62239

4741-S Registration Number

era

County

	and the second		ter i set ref i bet medenne steffer met referense internetiene met met and	
)ffice of Clerk and Recorder, Cou	nty of	lden	Valley	
"his "corner record" was filed for				
ssigned pere No.	in buck No	2	at 10:03 A	

la, in book No

Golden Valley County, Montana M Corner recorded on the sheet

Mer.

DIAGRAM OF CORNER:

R20E

15

22

T6N

16

21

... 19/....., was noted on the cross-index plat and is

N.

Date of work: April 20. 1977.

N Cross Index No