CERTIFIED LAND CORNER RECORDATION

 (\bigcirc)

DESCRIPTION O	F CORNER EVIDENCE FOUND, AND ORIGINAL RECO	RD (IF KNOWN)
ORIGINAL RECORD:		
Set a sandstone 22x20x3 i with 5 notches S. and 2 r	ns. 16 ins. in the ground for corner to senotches E.	os. 2, 3, 10 and 11 marked
FOUND:		
	nonument remains in county road. Position placed at the centerline intersection of Co	
•		
	RIPTION OF MONUMENT AND ACCESSORIES ESTABLE EXPETUATE THE ORIGINAL LOCATION OF THUS CON	INER: 41-1A-00
		Date of work: April 20, 197
Set an iron post 2 ins. d	liam., 30 ins. long with brass cap marked:	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
From the corner:		1977
A 60d nail, 1.4 feet high	, on west side of a power pole, bears NE, 3 n, on west side of a telephone pole, bears rs N89 ⁰ 37'W., 30.0 ft. dist.	
	E AND DISTANCE TO ADJACENT CORNERS IF DETER Y SKETCH OR PASTE REPRODUCTION ON REVERSE S	
		<u> </u>
	2 3 0	9
	2 N88 ⁰ 18'07''E 2701.13'	
	10 11	1
Bearing Base: North line	, NE¼, Sec. 2, T.6N., R.21E., (G.L.O. N83 ⁰ 3	57'W)
Summerica See		DIAGRAM OF CORNER:
Surveyor's Seal	I,	N.
	corroct.	T6N R2OE
	Signature of Ground Party Chief	$\frac{3}{10}$ 11
	I,	Golden Valley County,
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	Montana
	Guald P Cussell Signature of Surveyor	= Corner recorded on the sheet
	Christian, Spring, Sielbach & Assoc.	
62241	Billings, Montana <u>4741-S</u> Registration Number	· · · · · · · · · · · · · · · · · · ·
ffice of Clerk and Recorder, County	of Solden Valley	
his "corner record" was filed for rec	book No. 2 at 10. '08 A gena	as noted on the cross-index plat and is $\mathcal{A} = \mathcal{A}$
ssigned page No. 63, in	book No. 2 at 10:08 H Yerr	Inty Official
orm 125 45227	Cross Index No. E-17	T. 6 R. 20 Mer.
	4.0. 1 4s	