INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
  Description of monument and accessories set to perpetuate the corner position.
  Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
  Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
  Fill in Cross Index & Section Diagram at bottom of sheet.

239096

## **CERTIFIED CORNER RECORDATION**

T. GN R. ZSE P.M.M. MUSSELSHELL County Corner <u>NE SEC ZI</u> 1, ORIGINAL RECORD PER GL. O. SURVEY 1904: SET & SANDSTONE 18×14×3 INS 12 INS IN THE GROUND FOR COR OF SECS 15, 16, 21 AND 22, MARKED WITH 3 NOTLIFES ON S AND E EDGES AND RAISED A MOUND OF STONE 2 FT BASE I'ZFT HIGH WOF LOR. A PINE 26 INS. DIAM BEARS 543°E 209.9 DIST. MARKED TGN, R25E, S ZZ BT. A PINE 18INS DIAM, BEARS NZGOW, 118.8' DIST MARKED TGN, R 25 E, 5 16 B.T.

- 2 FOUND SET MARKED STONE WITH 5/8" REBAR SET ALONG WEST SIDE. BOTH BEARING TREES DOWN.
- 3) SET 11/2" STAMPED ALUM CAP ON FOUND REBAR, DROVE STEEL FENCE POST ON NISIDE OF STONE. NO OTHER ALLESSORIES WERE SET. CORNER FALLS ON SOUTH-EASTERLY OPEN SLOPE.

N81º08'08"E 2648.77

16

2639 4

Ц

ZZ



Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors