	OF CORNER EVIDENCE FOUND, sions, T6S, R6E" (70		RD (IF KNOWN)	
with 5 notche stone, 2 ft.	one, $15x12x7$ ins., 10 s on S. and 1 notch of base, $1\frac{1}{2}$ ft. high W. s. diam. bears N $17\frac{1}{2}^{\circ}$ ns. diam., bears S44° s. diam. bears S56 $\frac{1}{2}^{\circ}$ E ns. diam. bears N61°W	on E. edge, and of cor. From c	raise a moun	d of
of stone in g	c stone, 9x5 ins., fi ood condition 4 ft. W is a live 8-in. Doug thers dead.	. of cor. Rema	ins of all o	riginal
	CRIPTION OF MONUMENT AND PERPETUATE THE ORIGINAL L			
Drove a rebar a	long-		Date of work	. 8/19/77
side the sout of the stone magnetic resp Marked new BT's	for yr of the second se	γ ο Γ δ	surements fr f stone to f lazes with m ape.	om top ace of
(see below)	· cairn on yr:		•	
	0 4	0	is of bearin riginal bear ll BT.	
	Original SUBT			
(MA S2 BT: A live S1 BT: A live S12 BT: A live	E AND DISTANCE TO ADJACEN Y SKETCH OR PASTE REPRODU 13-in. Douglas-fir scr 7-in. Douglas-fir scr 6-in. Douglas-fir sc ched to record for NE	JCTION ON REVERSE S ribed "S2BT" ribed "S1BT" ribed "S12BT"	IDE.)	
			DIAGRAM	OF CORNER:
Surveyor's Seal	I, certify that the information sh correct.	own herein is true and	N.	T6S R6E MPM
	Signature of Ground			
	I, Henry A. Rate		<u>52</u>	Sl
	certify that I have carefully pe work done on the diagrammed co recordation form and approve the	rformed or reviewed the orner as reported on this	S1	1 5 12
	fer ATC Signature of S	urveyor	= Corner record	ed on the sheet
	147956	3716S Registration Number		

12: 300m <u>Mugalet Insueal</u> <u>County Official</u> Cross Index No. <u>E-21</u> T. <u>6 So</u> R. <u>6 E</u>. <u>Mer</u>.

.....

assigned	page	No	, in	book	No. one
		/			

Form 125-7887