INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated nere.

Description of me ment and accessories set to perpetuate the corner position.

3. 4. Description of monument and accessories sat to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner merking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
FW in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 33 & 34 T. 7N R. 9W P.M.M. Powell 1/4 Sections County

1. Original survey record not available

Subsequent Record:

A. Certified corner record 88796 filed by William Hubart 2350-S July 24th 1973 → "found underground remains of 3"x3" wood stake set a 7/8"x14" steel pin 12" in the ground."

B. Certificate of Survey #197 → "found 7/8 drill steel on N-S fenceline."

- C. Certificate of Survey #582RB → "3/8 "drill steel"
- 2. Found a 7/8"x7/8" square section drill steel firmly set under a N-S fence & 1.3 ft. N. of an E. W. fence. It is at a position that corresponds to the measurements shown on the above mentioned Certificate of Survey.

3. At the position of the found drill steel, I set a 2½ dia. x30" long aluminum post with a 3¼" aluminum cap marked as shown below. The position is in a secure place and no accessories are needed. It falls about 15 ft. south of centerline of a cattleguard on a private driveway under a rail fence.

