INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found note discremension is the subsequent record used to evaluate the corner position.
- Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners. Description of monument and accessories set to perpetuate the corner position. 3. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of 4. accessories, etc.
 - Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner NW. SEC. COR. SEC. 36

T. <u>7N.</u> R. <u>14W.</u> P.M.M.

GRANITE County

RECORD

GLO - unknown 1945, FAP 175 (4) Highway plans shows a tie to "Section Corner" Filed April 3, 1997, Corner Rec. 3321S, fnd. AC. for W.C. cor. 20' from true cor. Filed Feb. 2, 1998, Corner Rec. 3321S, corner is within roadway, set 5/8" rebar with AC. for witness corner on section line 20' in distance from section corner.

FOUND

2 1/2" AC on 5/8" rebar, 0.5' above grade marked as shown in sketch. Adjoining corners tied in survey shown below.



Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors