INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

246471

Description of evidence round, note discrepance.
Description of monument and accessories set to perpetuate the corner position.
Sector of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

- > G t/× ii → Corner ______ Secs. 13 & 24 S T. 7 N. R. 25 E. P.M.M. Musselshell _County
 - Original G.L.O. record Sept. 24, 1883 I. North between Secs. 19 & 24
 - والوج الما

89. P. S.

Chs. Set a sandstone 18x15x3 ins. 12 ins. in the ground for cor. to Secs. 13, 18, 19, & 24 marked 3 notches on N. & S. edges. dug pits 18x18x12 ins. in each Sec. $5\frac{1}{2}$ 80 ft. dist, & raised a mound of earth 2ft. high $2\frac{1}{2}$ ft base alongside.

- II. Found flat sandstone measuring $11"x2\frac{1}{2}"x8"$ above ground on N-S axis with 3 horizontal notches on N. and S. edges. The stone is 1' ESE of R.R. tie corner fence post with fences to N. S. and W. A gate in the fence bears southerly 120'.
- III. I raised a large mound of flat sandstones easterly, 1'

	CERTIFICATION
	I,
SKETCH OF CORNER	Employer: <u>Western Micro-Line</u> , P.C.
Office of Clerk and Recorder, County of <u>Musselshell</u> ecord" was filed for record on <u>October</u> 14, 1997	$\begin{array}{c} \text{Sec. 13} \\ \hline 2.49 \text{ Pm} \end{array}$
was noted on the cross-index plat and is assigned page No. JANE E. MANG	, in
book No County Offici	ial
Cross Index No. $N-25$ T. Adopted July 1, 1981, Montana Board of Professional Eng	7 N R. 25 E PMM sincers & Land Surveyors