242124

- .

 $i_{ij}$ 

13

INSTRUCTIONS
--------------

sition. ent record used to evaluate the corner p 1. Original and/or subsequ

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners

3. Description of monument and accessories set to perpetuate the corner position. 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Musselshell orner West 1-Section Cor. Sec 30 T. 7N. R. 26E. P.M.M. County

- I. No Original corner set for Section 30 in 1904. Original Corner set between Sections 25 and 30 refers to Section 25 T.7N., R.25 E. only.
- II. I located the Quarter Section Corner of Section 30 on the line between the Standard Section Corners to Sections 24 and 25 and Sections 25 and 36; and controlling the Northing at the proportionate mid-point between the Closing Section Corners to to Section 19 and 30 and Sections 30 and 31.
- III.At the location of the Corner I set a 5/8"x24" rebar with a 3" aluminum cap 3" above ground, with standard markings. Set a T-bar fence post 1-foot to North. Raised a mound of stone 1-foot to East. A North-South fence bears West, 4 feet.

Signature Ground Party Chief
I. Fred L. Hall Fred L. Hall by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq. M.C.A.) Signature of Surveyor & Seal Date: 10/6/95 Reg. No. 83.745
Employer: Western Micro-Line
This "corner 10: 50 Am
, in $\frac{1}{1}$ , in



į

