INSTRUCTIONS 1. Original and/or subsequent record used to evaluate the corner position.	242128
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated 	
corners.	
Description of monument and accessories set to perpetuate the corner position.	
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking,	
topography ties, position of accessories, etc.	-
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.	
6. Fill in Cross Index & Section Diagram at bottom of sheet.	

CERTIFIED CORNER RECORDATION

orner for Secs. 19, & 30 _____ T. <u>7N</u>____R. <u>26E</u>____P.M.M. _ Musselshell _County

I. Original 1904 G.L.O. Record:

West on a true line bet. Secs. 19 & 30 ...

- 74.57 Chains Intersect. W Bdy of Tp. Set a sandstone 18x16x5 in. 12 ins. in the ground for Closing Cor. of Secs. 19, and 30 marked C.C. on E. with 2 grooves on S and 4 grooves on N faces, and raise a mound of stone 2 ft. base $1\frac{1}{2}$ ft. high E of Cor. Pits impracticable. The Cor. of Secs. 24 & 25 ... bears N 8.70
- II. At the location for this corner I found no evidence of the original stone or bearing trees. I located the true position of this Closing Corner at the proportionate position on the line between the Standard Corners to Sections 24 and 25 and Sections 25 and 36.
- III.At the corner location I set a 5/8"x24" rebar with a 3" aluminum cap 6" above ground with standard markings. Set a T-bar fence post 1-foot to the North of the corner. Raise a mound of stone East 1.5 feet. A North-South fence bears Westerly 4.8 feet.

I,	I,	
Signature Ground Party Chief		
OVER I, Fred L. Hall	1.4.4	
by me or under my direction in complance with the "Corner.		
Recordation Act" (20-22-101, et sed., M.C.A.		
Signature of Surveyor & Seal		
Date: 10/6/95 Reg. No. 83745		
SKETCH OF CORNER Employer: Western Micro-Line		
Office of Clerk and Recorder, County of Musselshell. This "corner	l	
ord" was filed for record on October 10, 1995 11:00 AM		
was noted on the cross-index plat and is assigned page No, in $-+-+-+$		
JANE E. MANG bus houme. M.		
book No County Official (llomann)		
Cross Index No. <u>K-1</u> T. <u>TIV</u> R. <u>Abb</u> PMM • - Corner this sheet Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors		

Т