246472

INSTRUCTIONS	

Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

orners.						

c

. J. . .

corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. 7 N. R. 26 E. P.M.M Musselshell Corner Sec. 18 & 19 __County С

> Original G.L.O. record June 4, 1904 I. West on a true line bet. secs. 18 & 19

74.64 chains Intersect the W bdy of Tp.

Set a sandstone 24x10x4 ins. 18 ins. in the ground for closing cor. of secs. 18 & 19 marked C.C. on E. with 3 grooves on N. & S. faces A pine 12 ins. diam bears S 38° E 34 1ks. dist marked ... S. 19 B.T.

- Found a flat sandstone measuring 13"x3"x10" above ground on N-S axis with 3 horizontal notches on S. edge. The stone is set in a 3' dia ring of stone and is approximately 4" east of N-S fence. A charred fence post bears southerly $2\frac{1}{2}$ '. A charred 13" dia cut off II. tree used as a fence line post bears northerly 22'. The stump of a clearly marked B.T. bears S 37° E, 22'.
- III. No further work done

	CERTIFICATION
	I,
SKETCH OF CORNER	Employer Western Micro-Line, P.C.
Office of Clerk and Recorder, County of <u>Mussels hell</u> cord" was filed for record on <u>October 14, 1997</u>	$\begin{array}{c} \text{Sec. 18} \\ \hline 2:50 \ P \ M \end{array}$
was noted on the cross-index plat and is assigned page No book No JANE E. MANG Sy Harma M U County Offi	, in+-+
Cross Index No. $N-1$ Adopted July 1, 1981, Montana Board of Professional En	T. $\frac{7 \text{ N}}{\text{ngineers & Land Surveyors}} = - \text{ corner this sheet}$

1 1

