- IN #CTIONS 1. Original and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners Description of evidence tound, note discregations of the corner position.
 Description of monument and accessories set to perpetuate the corner position.
 Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
 Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner _	1/4 4/9	T8	Ν	_R	9 W.	P.M.M	Powell]	County	
	Record	1868 - Set a post in mound instructions.	of e	arth	with p	oits and	chared s	stake as p	per	
	Found	1987 - No evidence of original Corner Monument. As the nearest and best evidence of the corner position, use the Northern Pacific R.R. R/W drawing which shows a tie to the 1/4 corner, see sketch below of R.R. R/W and profile stations used. At the corner position, set a 3½"x30" Alum. monument, 30" in the ground, marked as per diagram below, from which: The top rail of a jack leg corral fence bears N 09°E, 35.3 feet with MARLS yellow tag. The top rail of a jack leg corral fence bears N 86°W, 25.3 feet with MARLS yellow tag. The corner falls in center of NW corral of several corrals in cattle loading facility.								
		1421. (PEF))				3/9+22.:	5		
	,	N89°57'W(R) N89	°43'5 LAR ((REF)	9.3(r.) 1.8(c)	342+60	M.P. 4 5		
	/		52%							
		USED RE DIFF. FRO TO LOCAT. LINE CROS	E SA	HIS ECTIL	PIPE		347+86.8	COUC.F	91PE	
	\					-3	57+06.4	A CASTI	ROW PIPE	
		TE OF MONS					CERTIE	FICATION		
,ia	gener allen at die gener die	STATE OF MONAL STATE OF MONAL WINENT DO HUMENT DO HUMENT DO HUMENT OF HIGHNAR SKETCH OF CORNER				I,				
Office	of Clerk ar	d Recorder, County of <u>Powell</u>		_		This ''co	rner	Sec. 4		
record" was filed for record on April 30th, 1987 @ 11:15 A.M.										
was noted on the cross-index plat and is assigned page No, in										
book N	book No County Official									
E-11 8 N. 9 W. Cross Index NoT,R,PMM • - corner this sheet										

BC:ts:5ee Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors