INSTRUCTIONS 1. Original and/or subsequent record used to evaluate the corner position. 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners. 3. Description of monument and accessories set to perpetuate the corner position. 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking,
topography ties, position of accessories, etc. 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana. 6. Fill in Cross Index & Section Diagram at bottom of sheet.
CERTIFIED CORNER RECORDATION

Corner <u>E 1/4 SEC. 7</u> T. <u>14 N</u> R. <u>18 E</u> P.M.M.

_County

FERGUS

- 1. ORIGINAL RECORD: Notes not obtained
- 2. No evidence found of original stone due to a N-S County Road.
- A fence line to the west of the County Road is 26 ft. north of record distance from what was believed to be the north line of the $S_2^{\frac{1}{2}}S_2^{\frac{1}{2}}$ of Sec. 7 as evidence by a fence to the west, and is 70 ft. north of record distance from the $E_2^{\frac{1}{2}}$ Cor. of Sec. 18. A fence line to the east of the first mentioned fence to the west, is 4 ft. south. Both east and west fences are ancient.
- 3. As best evidence, I accepted the fence to the west and drove a 5/8" x 30" rebar in the center of a N-S County Road and in line with the west fence.

Affixed an alumn. cap marked



Drove a 6' long steel post 31. ft. west.

	OF MONT		
$\frac{1}{1}$	I		
SKETCH OF CORNER	Employer:SELF		
Office of Clerk and Recorder, County of FERGUS This "corner			
record" was filed for record on NOV 29 1990 9an			
was noted on the cross-index plat and is assigned page Non, in book No			
Cross Index No. <u>G-5</u> T. <u>14N</u> R. <u>18E</u> PMM • - corner this sheet			
Adopted July 1, 1981, Montana Board of Professional En	ngineers & Land Surveyors 13939		