## CERTIFIED CORNER RECORDATION

## Corner: SE Sec. 2, T.14N., R59E., P.M.M., Wibaux County

**Original Record:** 

Found:

Found:

Set:

In 1883, Elmer Towne, U.S. Deputy Surveyor, set a sand stone 20x10x3 ins., 15 ins. in the ground for cor. to secs. 1, 2, 11, and 12, marked with 5 notches on South and 1 notches on East edges. Dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist., and raise a mound of earth 2 ft. high 4 1/2 ft. base alongside.

In 1969, from a plat (author unknown), Richard E. Guenzi found a 1-V2'' pipe set under a North–South fence. He projected the East boundary of the Wibaux Cemetery which is (by plat) on the East line of Section 11 and found that the pipe was on line. He also found a badly rotted 1x2 stake and hub in place as shown 66' Northeast of the pipe. The hub shown Northwest of the pipe was not found. It falls near the door of a shed. He did not add any further monuments to those existing. (See Bk 20, Pgs 388–390 Doc. 72972, 4–25–69)

In February 2004, MDT Survey Crew 41–86 found a 1-1/2'' iron pipe under a North–South fence line. The iron pipe is 36' south of four–way fence intersection. Accepted pipe as corner.

In March 2004, MDT Survey Crew 41–86 replaced iron pipe with a 3-1/4" A.C. on a 2-1/2"x30" flared aluminum pipe stamped as shown below 0.3' above ground with a MDT Survey witness post set 1' West of corner. Set 2-2" A.C. as references 35' North and South of corner with MDTSurvey witness posts alongside.



Corner this sheet

229

#110

5307. dan