INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

corners.

corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## **CERTIFIED CORNER RECORDATION**

\_\_\_\_\_T. <u>16 N</u> R. <u>12 E</u> P.M.M. Judith Basin Corner #6 SW Corner Section 8 County

80 chains "Deposited a marked stone 12 ins in the ground for RECORD: corner to secs. 7. 8. 17. 18. dug pits 18 x 18 x 12 in each sec.  $5\frac{1}{2}$  ft. dist. and raised a mound of earth 2 ft. high  $4\frac{1}{2}$  ft. base, over it. in S.E. pit drive a stake 2 ft long 2 ins square, 12 ins. in the ground. marked T.16 N. S.8 on N.E. R.12 E. S.17 on S.E. S.18 on S.W. S 7 on N.W. faces marked 4 notches on S. and 5 on E. deges."

- No evidence of original corner or accessories. A 24" #5 rebar with FOUND: yellow plastic cap set by 3976 ES was found.
- This corner was reestablished by 3976 ES and a recordation METHOD: filed in 1985.
- A 3¼ inch diameter aluminum cap riveted to a 30 inch flared SET: aluminum tube 2<sup>1</sup>/<sub>2</sub> inches in diameter and marked as shown and place the monument by 3976 ES inside. (Cap is 7" out of the ground)
- ACCESSORIES: 2 No. 4 rebar 12" long are located as follows: N. 00° 31' 59" E., 10.00 feet. N. 89° 20' 06" E., 10.00 feet.

MO

01



