13895

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

PRAADDATION -----

CERTIFIED CORNER RECORDATION					
Corner#1	.26 W ¹ ₄ Cor. Sec 8 T. <u>16 N</u> R. <u>12 1</u>	P.M.M. Judith Basin County			
RECORD:	40 chains "set sand stone 14 x 16 x 6 ins for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W face. dug p. N. and S. of stone $5\frac{1}{2}$ ft. dist. and raised ft. high. $3\frac{1}{2}$ ft base alongside."	its 18 x 18 x 12 ins			
FOUND:	No evidence of original corner or accessor	les.			
METHOD:	Reestablish corner at the intersection of East-West fence with fence running North. This position alignes with a fence corner and fence running South approximately 1330 feet to the South.				
SĘT:	A $3\frac{1}{4}$ inch diameter aluminum cap riveted to a 30 inch flared alum- inum tube $2\frac{1}{2}$ inches in diameter and marked as show n . 8 inches out of the ground.				
ACCESSORIES: The SW corner of Section 8 is S. 00° 31' 59" W., 2,659.39 feet.					
	THE OF MONA ATE OF MONA SANONUMENT DO NA SOLANONUMENT DO NA SOLANONUMENT DO NA SOLANONUMENT DO NA SOLANON	GERALD S. DITTO 2915 S SURVEYONING			
	SKETCH OF CORNER	CERTIFICATION I			
Office of Cle	erk and Recorder, County of _Judith Basin	Sec. 8			
	s filed for record on the20thNovember	day of 19 89			

			uay of 15 q5
was noted	on the cros	ss-index plat a	nd is assigned page No, in
book No.	File No.	4 48	Skralden Dmm
•			Cross Index No. 6-5 T. 16 N R. 12E PMM

