53906 INSTRUCTIONS Original and/or equent record used to evaluate the corner position. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated Description of evidence found, note discrepancies in the record, state method of establishing lost or ouncerated corners.
Description of monument and accessories set to perpetuate the corner position.
Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner #96 NW Corner Section 35 T. <u>16 N</u> R. <u>12 E</u> _ P.M.M. __ Judith Basin County

80 chains "set sand stone 14 x 12 x 8 ins. 10 ins. in the ground RECORD: for Cor. to secs. 26. 27. 34. & 35. marked 1 notch on S. and 2 notches on E. edges. and raised a mound of stone alongside. Pits impracticable."

No evidence of original corner or accessories FOUND:

- At the intersection of fence alignments North, South, East and METHOD: West (all distant form intersection point), I find evidence of an old road which obliterated all evidence of corner. I accept the position of the fence alignments for this section corner. Corner falls in open pasture. I place a steel survey marker post alongside.
- SET:

A $3\frac{1}{4}$ inch diameter aluminum cap riveted to a 30 inch flared aluminum tube $2\frac{1}{2}$ inches in diameter and marked as shown. (Cap is 6" out of the ground)

ACCESSORIES: The $\frac{1}{4}$ corners to the West and South are as follows: S. 89° 18' 21" W., - 2,632.09 feet S. 00° 58' 26" E., - 2,720.40 feet.





SKETCH OF CORNER

CERTIFICATION				
e information shown herein is true and correct.				
Signature Ground Party Chief				
Gerald S. Ditto				
at this Corner Record correctly represents work per or under by direction in compliance with the tion Act'' (70-22-101, et seq., M.D.A.)				
Signature of Surveyor & Seal				

formed

Date: 2-23-89 Reg. No. 2915 S

Self Employer:

certify the l

certify that t

by me or Recordation

Office of Clerk and Recorder, Cour	ty ofJudith Basin	This ''corner	Sec. 35	-
record" was filed for record on the	November 20	day of 19 ⁸⁹		
was noted on the cross-index plat a book No. File No. 459	nd is assigned page No	fildal , in	┼─┼─┼─┤	
	Cross Index No. V-17	T. 16 N. R. 12 E PMM	- corner this sh	leet