## **INSTRUCTIONS**

## Q:CO-STD/152

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners
- Description of monument and accessories set to perpetuate the corner position.
   Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography use, position of accessories.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

## **CERTIFIED CORNER RECORDATION**

Corner: <u>One-quarter (1/4) Corner Sections 16 & 17</u> T. <u>16N</u> R. <u>20W</u> P.M.M. <u>Lake County</u>

1905 GLO
Set a shale stone 14x10x8 ins., 10 ins. in the ground marked ¼ on west face, from which:

A 28" Tamarack bears N70°E, 146 lks (96.3'), marked ¼ S 16 BT.
A 12" Pine bears West, 10 lks (6.6'), marked ¼ S 17 BT.

2007 Found: Found a 15" x 10" x 7" firmly set shale stone clearly marked ¼ on west face. No distinguishable reference monuments were found.
2007 Perpetuation: At the position of the found original one-quarter corner stone, we set a 5/8 x 30 inch rebar topped with a 3-1/4 inch aluminum cap flush with the ground surface. We stamped the monument as shown below and establish the following references:

A Larch bears N28°E, 23.5 feet, with existing heal blaze.
A 8" Larch bears S24°E, 20.6 feet, blazed and scribed "RM".

References affixed with BT tags, a snow blaze, and a red band. We set a galvanized steel post north of the monument 0.3 ft. We buried the original stone 1.5' south of monument.

NORTHWESS NORTHWESS NORTHWESS TIGN R20W TO NOR TIGN R20W TO NOR STIT SIG NOR TIGN R20W TO NOR STIT SIG NOR TIGN R20W TO NOR STIT SIG NOR TIGN R20W TO NOR STIT SIG NOR STIT SIG NOR STIT SIG SKETCH OF CORNER		n herein is true and Chief rd correctly 4 by me organization my the "Corner 4, et Stats, Mic A.) ENKINS ENKINS 2 Seal 7/3 TER 30 LS
Office of Clerk and Recorder, County of Jake		Sec. 16
record" was filed for record on SEP 1 7 2007 @ 2.	This "corner	
was noted on the cross-index plat and is assigned page No. 483147 Book No.	the Activity	
County Official		
C = 274 N/C C = 274 N/C C = 274 C = 7. 16N	R. <u>20W</u> PMM	- Corner this sheet