CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found: No evidence of original monument. P_0 ssibly destroyed by road built for Mission Dam.

Record: Sandstone 24x16x10 inches, 18 inches in ground. Carved $\frac{1}{4}$ on North

face; from which a pine 12" in diameter bears S23°E, 38 links. A

pine 12" in diameter bears N77°W, 58 links.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 1/30/74

At the $\frac{1}{4}$ corner common to Sections 16 & 21 set a brass cap on a 30" pipe 10" above ground. Raised a mound of stone around brass cap. Also established two R.M.'s. These_are:

Bross Cap Set

1. A 22" ponderosa pine scribed "RM" with an "X" above the blaze . It bears

\$65°E, 10.2'

2. A yellow cap stamped "Sorenson & Company" on top of a fence corner. bears SO3°W, 22.69'.

Yellow Cop on --

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See reverse side.

DIAGRAM OF CORNER-Surveyor's Seal David R. Davis certify that the information shown herein is true and S 1/4 Sec. 16 NTANA well silano Signature of Ground Party Chief GORDON E. SORENSON Gordon E. Sorezson certify that I have carefully performed or reviewed the 2345 ES TIBN RIGW work done on the diagrammed corner as reported on this recordation form and approve the same. AGR. & LAND Corner recorded on the sheet Signature of Surveyor 2345 ES

2345 ES Registration Number

"corner record" was filed for record on the ... day of February 1974, was noted on the cross-index plat and is ned page No. C-474, in book No. 215138.

ETHEL M. HARDING Margaret Bruegeman CLERK & RECORDER County Official Deputy Cross Index No. N. 11. T. 18 N. R. 19 W. Mer.

SECTION 16, T.18N., R.19W. 1000' 5280.00 1000. 5295.64 N 89°56'08"E 2647.82' Fnd. 2647.82 2640.00 Rac. 2640.00 Pac. 1521.96' Rec. N 00°09'29"E 5290.51' Fnd, N 00° 00' 22' 5280.00' Rac. 2645,25' 2640.00 N 00°138" | 02" E Rac. (alc. S 00°08'31" W S 00°08'31" W 1054.90' F.d. 1121.60' 054.68' Rac. 5285**.59**' 1322.23 1322.23 2641.13 1322.63' Fro ~.64.IQ.00N N 00° 04' 00" W N 00° 04' 00" W 1324.60 N 00°00'22" 1326.58 Stone, M.C. <u>889°59'50''E</u> 1321.39' 1321.39 N 00°00'22'E 322, 63 Frd. N "64' 10 ao N 1326.58 Reber. SWCO Section 18 1320.55' Frd. 1320.55' Frd. 10512.28 21,22 Double Proportion S 00° 00'17"E LEGEND 0 ∞ Set Corner SORENSON & COMPANY Rebar, W14 Corner Section 28 Missoula, Montana

59801