	INSTITUCTIONS 1. Original and 4. Quent record used to evaluate the corner position 2. Description of instrument and accessories in the record, state methy dishin, corners 3. Description of monument and accessories set to perpetuate the corner position 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example topography lies, position of accessories, etc 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana 6. Fill in Cross Index & Section Diagram at bottom of sheet	61- ig lost or obliterated le, corner marking.	272390
CERTIFIED CORNER RECORDATION			
Corner	<u></u>	1. <u>Lake</u>	County
RECORD	<pre>GLO (1905): Set a slate stone, l4xl0x8 ins., 9 in for closing cor. of secs. 4 and 5, ma with 4 grooves on E. and 2 grooves on 24xl8xl2 ins., crosswise on each line ft., and S. of stone, 7 ft. dist., an earth, 4 ft. base, 2 ft. high S. of a</pre>	arked CC on n W. face; e, E. and W nd raise a	S., dig pits, ., 3
FOUND:	No evidence found; position falls in R/W State H: [F.A.S. S-306(2)].	ighway 211	
SET:	2½" pipe with 2½" aluminum cap stamped as shown. north of centerline F.A.S. S-306(2) per plans and		

road to south. See reverse side for ties to other corners.

521N PZOW 33 CC 54 TZON 1982 4468-

