61- 345748

CERTIFIED CORNER RECORDATION

Corner <u>E 1/4</u>	Sec. 32 T. 22 N. R. 20 W. P.M.M. Lake County
ORIGINAL RECORD:	Set a sand stone, 16x8x5 ins., 11 ins. in the ground for 1/4 sec. cor., marked 1/4 on W. face; dig pits, 18x18x12 ins., N. and S. of stone, 3 ft. dist.; and raise a mound of earth, 3 1/2 ft. base, 1 1/2 ft. high, W. of cor.
FOUND:	A 1" iron pipe, set 1' flush with ground. This 1" pipe is believed to be the reference monument to the 1/4 corner.

At a point 30' west of the 1" pipe and on a straight line from C 1/4 thru the found reference monument, I set a 5/8" **MONUMENTATION:** rebar with cap stamped "CS&KT RLS 9012." See sketch below.

See COS #4730 for Section Control Data

CERTIFICATION 0 X certify the information shown hereinwhattrue and correct. 5% RELAR & CAP Charles STAMPED 65 PKT Bignature Ground Party GRAVEL ROAd. R15 90120 I, UIEQUE cartify that this Corner performed by me or under performed by me or under 0 1 0 ord correct1 presents work West 30.0 K Repord 1913 eq. ; H.C.A.) IRON 1 Signatur Pipe 1 <u>9/92</u> Reg. No. 9012 Dates CS&KT Employer: NO SCALE SERTCE OF CORNER Sec. 32 record was filed for record on _____MAR 9'93 ____ at 11:16 Am was noted on the cross-index plat and is assigned C-1936, in RUTH E. HODGES Jaula a Holle County Official - corner this sheet Cross Index No. X-9 T. 22 N. R. 20 W. PMM MIC