INSTRUCTIONS	
THOTTOUTIONS.	

- INSTRUCTIONS
 1. Original and/or subsequent record used to evaluate the corner position.
 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
 3. Description of monument and accessories set to perpetuate the corner position.
 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
 5. Certification must be claraded and coeld but lead formations in the formation of the formation of the statement of the formation of the statement of

Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION 22 N., ____R._

N 1/4 Cor. of S17 30 W., Sanders Corner _ _____P.M.M. _ Τ. County

1893 G.L.O. record by R. W. Page and A. Page: Set a post and two bearing trees: Ι.

1984 BLM Resurvey record: Point for the 1/4 sec. cor. of secs. 8 and 17, determined by the irregular boundary method of proportionate measurement. There is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap aid.



Raise a collar of stone, 3 ft. diam., around the aluminum post.

II. Found a 2 1/2 ins. diam. pipe, 3 ins. out of the ground, with BLM alum. cap mkd. as shown:

III. Corner falls in open field therefore, no bearing trees available.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, East, 3 ft.

Magnetic Declination: 20° East

Para	6min- 1	6
Englished	-	

3 559

	CERTIFICATION IThomas M. Hommel certify the information shown herein is true and correct.	
NO BEARING TREES (OBJECTS) AVAILABLE	Signature Ground Party Chief IAlvah F. Hughes certify that this Corner Record correctly represents work performed by me or under my direction in complian e with the "Corner" Recordation Act" (70.22-101 et seq., M.C.A.) Image: Alvah F. Hughes Certify that this Corner Record correctly represents work performed by me or under my direction in complian e with the "Corner" Recordation Act" (70.22-101 et seq., M.C.A.) Image: Signature of Surveyor & Spall Signature of Surveyor & Spall Date: 1/22/92 Reg. No.	
SKETCH OF CORNER	Employer: U.S. FOREST SERVICE	
Office of Clerk and Recorder, County of	This "corner Sec. 17	
record" was filed for record on March 9, 1993		
was noted on the cross-index plat and is assigned page No. -55	9	
book No 3 Reper Vauper County Offic	ky E. Col Ap	
J-7 Cross Index No T.	22 N 30 W	
1. I.	R РММ • - cor er this sheet	

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors