## CERTIFIED LAND CORNER RECORDATION

	72-1244
DESCRIPTION	OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)
At the Section corner 30 West, Sanders Coun	common to Sections 2, 3, 10 & 11, Township 22 North, Range ty, Montana.
2, 3, 10 & 11 marked 5 notches on South & 1 A fir 6" N.55°E., A fir 8" S.70 1/21 A pine 14", S.61 1	E., 56 links
WE FIND: 2-BT stumps	, 2-stump crowns, pile rock & a hub & tack.
DE TC	SCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
WE ESTABLISH this cor	ner by ties from original GLO notes.
TO PERPETUATE this con establish the followin	rner we set a 24" copper weld monument mounded with rock and ng reference monuments:
A 8" Pine bears S A 12" Pine bears S A 5" bears N.42°00	.38°00'E., 21.55 feet 5.44°30'W., 28.00 feet
Variance used 20°	
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)	
	$ \begin{array}{c}   29235 \\   \hline   7 \\   22 \\   N \\   10 \\   1'' \\   30 \\   10 \\   1'' \\   10 \\   1''' \\   1''' \\   1''' \\   1''' \\  $
Surveyor's Seal	ELDEN INABNIT     DIAGRAM OF COENER:       I,        certify that the information shown herein is true and correct.     N.       Signature of Ground Party Chief        I,        I,        Signature of Ground Party Chief        I,        I,        Certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.       Auanowoot       Signature of Surveyor
	AINSWORTH & ASSOCIATES Registration Number
	y of Jandera Lille and 149382
This "corner record" was filed for record on the	
assigned page No	
FORM 125-41483	Cross Index No. F-17 T. 22N B. 30W P. Mer

-