61- 372256

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

Description of evidence found, note discrepancies in the record, bate include a construction of corners.
Description of monument and accessories set to perpetuate the corner position.
Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner South 1/4 Cor. Section 16 T. 23N. R. 20W. P.M.M. LAKE ____County RECORD: from G.L.O. Field Book 4599, page 9, surveyed April 1905 Set a slate stone, 16"x 8"x 5", 11" in the ground, marked "1/4" on north face, raised a mound of stone 2' base, 1.5' high, north of corner. Original stone found in place per Certificates of Survey No. 2562 and 4520 FOUND: Stone 3" x 5" x 5" out of ground with "1/4" visible on north face An existng north - south fence line over stone SET: 5/8" rebar & cap (7681S), 0.19" north of found stone, from a "+" in top of Stone: -a clump of small junipers bears West 35.5' -a 15" ponderosa bears S39°E 123.0', no scribing Used a SILVA hand compass (declination 18°30'E) REFERRENCE C.O.S. <u>51</u>49

·	NONTAN .
WEST 0.19' 35.5' CLUMP OF 16 SMALL JUNIPER SET ⁵ / ₈ " REBAR & CAP (768IS) EXISTING FENCE	CERTIFICATION DANIEL P I. <u>Daniel P. Brien</u> Certify the Information shown herein is true and covered is Signature Ground Party Chief. Argentic I. <u>Daniel P. Brien</u> certify that this Corner Record correctly represents work performed by me br under my direction in compliance with the "Corner Recordation Act" (70-24-101, et sag., MC.A.) Multiple Signature of Surveyor & Seal Date: <u>8/14/95</u> Reg. No. <u>768/S</u>
	Employer: HERSMAN LAND SURVEY
Office of Clerk and Recorder, County ofLAKX record'' was filed for record on FEB 28 '96 at	This "corner $f: 38 A.M$.
was noted on the cross-index plat and is assigned 372256	
- Allan my own piece , beguily.	23N. R. 20W. PMM • - corner this sheet

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors