- INSTRUCTIONS
- nal and/or subsequent record used to evaluate the corner position.
  Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- orners.

18 17

Corner \_\_\_\_\_

1893 GLO Record:

- Description of monument and accessories set to perpetuate the corner position
- Description of monument and accessories set to perpetuate the corner position.
  Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
  Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
  Fill in Cross Index & Section Diagram at bottom of sheet.

71 CERTIFIED CORNER RECORDATION

24 N.

\_\_\_\_\_R. 31 W.

\_\_\_\_P.M.M. \_\_\_\_Sanders

County

## Set a Granite Stone; 18x18x10 ins., 12 ins. in the ground 20" Tamarack N.8612 E., 61 1ks. 22" Tamarack S.33<sup>1</sup><sub>2</sub> E., 26 lks. 22" Tamarack S.67°20' W., 205 lks. 20" Tamarack N.83½ W., 115 lks. Found: Stone had been removed. Found rock mound, under N-S fence 1.5 ft. S of fence corner. Found rotted stumps at location of each bearing tree. Set: Set a 1"x48" iron pipe & cap "LS 5616" in depression where stone had been and at record distances from stumps. R.P.'s: Set nail & tag "LS5616" in: 14" Pine N.68 W., 16.80 ft. 12" Pine S.12 W., 51.00 ft. See L.C.R. recorded on page 3-923 MC MES R FULTON 199.82 6165 CERTIF <sub>I,</sub> J Fulton WCMC 0 = LAND FD. W.W.P. Co. Noi I, J Fulton 14.6.41 BRASS CAP IN CONC. James R. Fulton MONUMENTS. Signature Ground Party Chief 217.70 James R. Fulton certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner mplian NC. Record 199.67 Lon 0.39 7 B 239.43 /26/95 Reg. No. LS 561 ate 6 2652.66 18 17 Washington Water Power Co. Employer: SKETCH OF CORNER Sec. Office of Clerk and Recorder, County of <u>Sanders</u> \_ . This ''corner record" was filed for record on July 17, 1995 at 1:35 pm was noted on the cross-index plat and is assigned page No. Fillie Wollas CIKEROC book No. . By: Rovi (1. deputy Official W 218272 J-5 24 N R. 31 W PMM corner this sheet Cross Index No Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors